



## Resistance Thermometer for additional Thermowell

Field No.	Code	Description	Base Price	136.50
			Add Price	
		<b>Explosion Protection</b>		
	6	CSA	n/a	
	G	According to Directive 94/9/EG (ATEX) EEx(d)	n/a	
		<b>Type and Number of Sensors</b>		
	3	1 x Pt 100 application range -100 degC ... +600 degC	37.50	
	4	2 x Pt 100 application range -100 degC ... +600 degC	55.80	
	5	1 x Pt 100 application range -100 degC ... + 450 degC	5.20	
	6	2 x Pt 100 application range -100 degC ... + 450 degC	20.90	
	7	1 x Pt 100 application range -200 degC ... +200 degC	n/a	
	8	2 x Pt 100 application range -200 degC ... +200 degC	n/a	
	R	1 x Pt 100 application range -50 degC ... + 450 degC	n/a	
	S	2 x Pt 100 application range -50 degC ... + 450 degC	9.85	
		<b>Sensor method of connection</b>		
	2	2 wire	n/a	
	3	3 wire	n/a	
	4	4 wire	n/a	
		<b>Sensor limiting error</b>		
	A	Class A per DIN EN 60751 (max 450 degC)	13.90	
	B	Class B per DIN EN 60751	n/a	
		<b>Measuring Insert Diameter</b>		
	1	3 mm	9	
	3	6 mm	n/a	
	4	8 mm	4.65	
	A	1/8" (3.18 mm)	n/a	
	B	1/4" (6.35 mm)	n/a	
		<b>Insertion Length</b>		
	0110	110 mm	n/a	
	0140	140 mm	n/a	
	0145	145 mm	n/a	
	0170	170 mm	n/a	
	0200	200 mm	n/a	
	0205	205 mm	2.90	
	0230	230 mm	2.90	
	0245	245 mm	2.90	
	0260	260 mm	2.90	
	0295	295 mm	2.90	
	0305	305 mm	5.80	
	0345	345 mm	5.80	
	0350	350 mm	5.80	
	0395	395 mm	5.80	
	0410	410 mm	8.70	
	0445	445 mm	8.70	
	0545	545 mm	11.60	
		<b>Neck Length MH</b>		
	0	without (female thread in the connection head)	n/a	
	5	150 mm	n/a	
		<b>Neck Tube</b>		
	K0	M20 x 1.5 (head), 1/2 NPT (tw), diam=14mm, 316 S.S	40.50	
	K1	M20 x 1.5 (head), G 1/2 B (tw), diam=14mm, 316 S.S	40.50	
	K3	M20 x 1.5 (head), M18x1.5 (tw), diam=14mm, 316 S.S	48.95	
	N1	1/2 NPT (head), 1/2 NPT (tw), N-U-N, diam=22mm, 316 S.S	31.35	
	N2	1/2 NPT (head), G 1/2 B (tw), N-U-N, diam=22mm, 316 S.S	57.40	
	ZZ	without	n/a	
		<b>Connection from connection head to extension neck</b>		
	2	M20 x 1.5	n/a	
	4	1/2 NPT	n/a	



## Resistance Thermometer for additional Thermowell

Field No.	Code	Description		
		<b>Cable entry to connection head</b>		
	3	1/2 NPT	n/a	
	4	M20 x 1.5	n/a	
	6	3/4 NPT	n/a	
		<b>Transmitter</b>		
	TA	mounted on the measuring insert	5.50	
	ZZ	without	n/a	
		<b>Quality Certificates</b>		
	1	Yes	n/a	
	Z	No	n/a	
		<b>Additional Text</b>		
	T	Yes	n/a	
	Z	No	n/a	
			<b>Total Price</b>	